

Application No. 10/615,447 ----- 2

Amendments to the Claims

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

Claims 1-4 (canceled).

Claim 5 (currently amended): A bicycle rack adapted to be fitted on an elongate support frame for holding a bicycle by its wheel in an upright position on a bicycle support surface, the rack comprising:

a bracket adapted to be fitted on the elongate support frame;

a brace including a lower brace member coupled to and extending outwardly from said bracket and an upper brace member coupled to and extending upwardly from said bracket;

said upper brace member defining an opening for receiving a first portion of the bicycle wheel;

said lower brace member defining an opening for receiving a second portion of the bicycle wheel; and The bicycle rack of claim 6

wherein said lower brace member includes a pair of spaced-apart arms terminating in a downwardly extending generally U-shaped lip including a closed end adapted to abut the bicycle support surface and being adapted such that a bicycle wheel can be rolled over said closed end of said lip and between said arms.

Claim 6 (canceled).

Claim 7 (currently amended): A bicycle rack adapted to be fitted on an elongate support frame for holding a bicycle by its wheel in an upright position on a bicycle support surface, the rack comprising:

a bracket adapted to be fitted on the elongate support frame;

Application No. 10/615,447 ----- 3

a brace including a lower brace member coupled to and extending outwardly from said bracket and an upper brace member coupled to and extending upwardly from said bracket;

said upper brace member defining an opening for receiving a first portion of the bicycle wheel;

said lower brace member defining an opening for receiving a second portion of the bicycle wheel; and The bicycle rack of claim 6

wherein said upper brace member includes a pair of spaced-apart arms.

Claim 8 (original): The bicycle rack of claim 7 wherein said upper brace member includes a proximal portion where said arms are bent inwardly at an acute angle relative to said bracket and a distal portion unitary with said proximal portion where said arms are bent outwardly at an obtuse angle relative to said proximal portion.

Claim 9 (previously presented): A bicycle rack adapted to be fitted on an elongate support frame for holding a bicycle by its wheel in an upright position on a bicycle support surface, the rack comprising:

a bracket adapted to be fitted on the elongate support frame;

a brace including a lower brace member coupled to and extending outwardly from said bracket and terminating in a lip, and an upper brace member coupled to and extending upwardly from said bracket, said brace being adapted such that the wheel of the bicycle can be rolled along the bicycle support surface directly into said lower brace member for holding the bicycle in an upright position on the bicycle support surface; and

wherein said upper brace member includes a pair of spaced-apart arms coupled to and extending generally upwardly from said bracket, said upper brace member including a proximal portion where said arms are bent inwardly at an acute angle relative to said support frame and a distal portion unitary with said proximal portion where said arms are bent downwardly at an acute angle relative to said proximal portion, said arms terminating in a generally U-shaped lip which abuts the lip of said lower brace member, the bicycle wheel being rolled through the lips of said upper and lower brace members and between said arms of said upper brace member.

Application No. 10/615,447 - - - - 4

Claim 10 (currently amended): The bicycle rack of claim 9 claim 6 further comprising a fastener extending through said bracket and into the support frame, releasably securing said bicycle rack to the support frame.

Claim 11-13 (canceled).

Claim 14 (previously presented): A rack for holding a bicycle by its front or back wheel in an upright position on a floor and adapted to be fitted on an elongate support frame seated on the floor, the rack comprising:

a hollow sleeve adapted to be fitted on the elongate support frame seated on the floor, said sleeve including a top face and an outer face;

a lower brace including a pair of spaced-apart arms including proximal ends coupled to and extending generally outwardly from said sleeve in spaced relation to the floor and terminating in a downwardly extending lip including a closed end adapted to abut the floor, the lower brace being rotatable along a horizontal plane relative to the bracket; and

an upper brace including a pair of spaced-apart arms in alignment with the pair of arms respectively of said lower brace, said arms of said upper brace including proximal ends coupled to the outer face of said sleeve and extending generally upwardly from said sleeve and terminating in a closed end

such that the front or back wheel of the bicycle can be rolled along the floor directly through said lip of said lower brace and received between said arms of said lower brace and said upper brace respectively for holding the bicycle in an upright position relative to the floor.

Claim 15 (original): The rack of claim 14 wherein said upper brace includes a proximal portion where said arms extend inwardly at an acute angle relative to said sleeve and a unitary distal portion where said arms of said upper brace extend outwardly at an obtuse angle relative to said proximal portion.

Claim 16 (previously presented): The rack of claim 14 wherein said sleeve is rectangularly shaped.

Claim 17 (currently amended): The rack of claim 14 claim 6 wherein the lower brace member is rotatable along a horizontal plane relative to the bracket.

Application No. 10/615,447 - - - - 5

Claim 18 (currently amended): A bicycle rack adapted to be fitted on an elongate support frame for holding a bicycle by its wheel in an upright position on a bicycle support surface, the rack comprising:

a bracket adapted to be fitted on the elongate support frame;

a brace including a lower brace member coupled to and extending outwardly from said bracket and an upper brace member coupled to and extending upwardly from said bracket;

said upper brace member defining an opening for receiving a first portion of the bicycle wheel;

said lower brace member defining an opening for receiving a second portion of the bicycle wheel; and The bicycle rack of claim 6 wherein:

the bicycle wheel has a center; and

said upper brace member comprises a first part extending toward the center of the bicycle wheel and a second part extending away from the center of the bicycle wheel, with the first and the second parts cooperating to define an opening for receiving the first portion of the bicycle wheel.